

Aerostat® FPD

The Aerostat FPD series of products has been designed to control electrostatic charges in assembly and electronics manufacturing applications requiring stable operation with exceptionally fast discharge time performance. The FPD overhead products are built for reliability and simplicity.

Aerostat FPD utilizes reliable, low maintenance AC corona technology with high flow rate fans to provide fast static discharge performance. The inherent stability of the FPD product reduces maintenance frequency and a built in emitter cleaner reduces maintenance time. Our unique geometry and airflow control provide consistent performance, meeting the demands of product assembly operations.

Products feature self-monitoring to assure the user of controlled, consistent ion output. A light indicates both that power is applied to the unit and that ions are being produced. Performance is enhanced by use of Simco's industry leading and highly reliable AC technology.

- ▶ *Fast Static Discharge*
- ▶ *High Reliability*
- ▶ *Built-in Emitter Point Cleaner*
- ▶ *Ions Present Indicator*

Aerostat FPD



Aerostat FPD ion air blowers provide the highest airflow and widest coverage area for big jobs, where providing the fastest discharge time is critical to meet process requirements. Available in two, three, and four fan models FPD provides coverage in a variety of applications.



Ionization for Electronics Manufacture

Specifications:

Performance*

Discharge Time: 1.0 second; (center position, high fan speed)
 Offset Voltage: 10 ±5V

Operational Specifications

Ion Balance: Auto-adjust
 Power: 0.5 Amps. maximum consumption
 Operating Temp: 0°C (32°F) to 50°C (122°F)
 Ozone: Equilibrium concentration <0.02 ppm

Audible noise: 59 to 69 dB (A) Max.

Mechanical Specifications

OFF/ON: Two position switch
 Fan Speed: Recessed potentiometer
 Indicator: Ionization ON light
 Enclosure: Aluminum
 Color/Finish: White enamel
 Mounting Brackets: Stainless steel

Option

Air Pre-filter: 30ppi open cell polyurethane foam

Dimensions / Weight			
	2-fan FPD	3-fan FPD	4-fan FPD
Dimensions	590 x 100 x 160 mm (23.25" L x 4.0" H x 6.25" W)	900 x 100 x 160 mm (35.5" L x 4.0" H x 6.25" W)	1215 x 100 x 160 mm (47.75" L x 4.0" H x 6.25" W)
Weight	4.5 kg (10 lbs.)	5.9 kg (13 lbs.)	7.3 kg (16 lbs.)
Coverage Area	0.6m x 1.5m (2' x 5')	0.9m x 1.5m (3' x 5')	1.2m x 1.5m (4' x 5')

Part Numbers	Cord Set		
	N. America	Continental Europe	UK
2-fan, 120/220 VAC, 50/60 Hz	4011005	4011279	4011280
3-fan, 120/220 VAC, 50/60 Hz	4011007	4011281	4011282
4-fan, 120/220 VAC, 50/60 Hz	4011009	4011283	4011284

*Tested in accordance with ANSI ESD-STM3.1-2000, IONIZATION

In Ionization technology, SIMCO® clearly has the leadership role. Our research and manufacturing facilities are worldwide...our technical expertise is second to none...and our products simply inspire the competition. For a no-hassle assessment and quote call 800-538-0750 (in USA) or log on to www.simcolON.biz.



Products manufactured by SIMCO under USA and International patent(s).
 Specifications subject to change without notice. July 2006 Copyright © 2006 SIMCO
 5200953-Printed in USA



SIMCO® Ionization for Electronics Manufacture 2257 North Penn Road Hatfield, PA 19440 USA
 In USA: 800-538-0750· Tel: 215-997-0590· Fax: 215-997-3450· Web: www.simcolON.biz· email: info@esimco.com